



JMLU2.MH27557
Gaskets and Seals - Component

Gaskets and Seals - Component

See General Information for Gaskets and Seals - Component

INTERNATIONAL SEAL CO INC, DBA DICHTOMATIK N A
1087 PARK PL
SHAKOPEE, MN 55379 USA

MH27557

Compound Dsg	Max Serv Temp	Min Serv Temp	Hardness Range	Tnsl Str	Elong	Max Comp Set	Max Tnsl Set	Use (1)
Nitrile								
ASI-N70	+60C	-40C	66 to 76	2260	290	5.8	2	A, D, F, J, G and J(3)

- (1) See explanation of end-use environments in guide for this category.
- (2) Suitable for use with water.
- (3) Suitable for dry chemical and water extinguishing agents.

Marking: Company name or tradename "Dichtomatik", compound designation and the UL Recognized Component Mark on material, on a substantial tag, on container or smallest packaging.

© 2012 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the UL Environment database for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".